

Skid mounted Slickline Units



Double drum in split design, Slickline / Monoconductor cable unit "Ranger"

Manufacturer
Rebound

Engine Power
58 kW / 78 HP diesel, water cooled with mechanical starting system
Zone 2 certified

Transmission
Hydraulic engine : Dynapower, piston type 6"
Hydraulic pump : Dynapower, piston type 6", Max. W.P. = 422 bar / 6120 PSI

Weight indicator
Hydraulic - Martin Decker 0 – 2000 lbs
Electronic – Red Lion 0 – 4000 lbs

Depth indicator
Mechanical – Veeder Root
Electronic – Red Lion

First drum (split design) capacity (Monoconductor cable)
First half of drum 4.76 mm / 3/16 " 7067 m
Second half of drum 4.76 mm / 3/16 " 7067 m

Second drum (split design) capacity (Slickline)
First half of drum 2.34 mm / 0.092 " 7620 m
Second half of drum 2.74 mm / 0.125 " 6345 m

Dimensions
4.3 m (L) x 2.5 m (W) x 2.4 m (H); Weight = 9.0 t

Safety devices
Air inlet shut off, spark arrestor, anti – static fan belts fitted, safety valves on low and high pressure circuits, safety relief valve

Single drum, two – component Slickline unit "WL-2"

Manufacturer
Camco

Engine Power
Torpedo – Deutz, model F 4 L 912; 53 kW / 71 HP diesel, air cooled with mechanical starting system
Zone 2 certified

Transmission
Hydraulic engine : Denison MIC-042

Weight indicator
Hydraulic - Martin Decker 0 – 2000 lbs

Depth indicator
Mechanical – Veeder Root

Drum capacity
2.34 mm / 0.092" 6100 m

Dimensions
Power pack: 2.0 m (L) x 1.0 m (W) x 1.3 m (H);
Weight = 0.7 t
Winch and panel : 2.0 m (L) x 1.2 m (W) x 1.5 m (H);
Weight = 1.0 t

Safety devices
Air inlet shut off, spark arrestor