



Truck mounted crane Slickline units 1 - 8



Manufacturer

Maritime Hydraulics

Truck

International, 2674 Series

Engine Power

Cummins, model N14+; 295 kW / 395 HP diesel, air cooled with electric starting system

Hydraulic system

Hydraulic pump : Sauer Sundstrand, model series 90L100; capacity 200 l/min at 2200 RPM
Hydraulic engine : Sauer Sundstrand, model series 90M100 6.1"; Max. pressure 345 bar / 5000 lbs
Control valve : Sauer Sundstrand, model MCH / EDC

Weight indicator

Hydraulic - Martin Decker 0 – 2000 lbs
Electronic – RS Corporation 0 – 999999 lbs

Depth indicator

Mechanical – Maritime Hydraulics 0 – 999999 m
Electronic – RS Corporation 0 – 999999 m

First drum capacity

2.74 mm / 0.108" 6100 m / 20 000 ft

Second drum capacity

3.17 mm / 0.125" 6100 m / 20 000 ft

Crane

Manufacturer : National Crane
Series : 600C
Capacity : certified for 5 t
Extended length : 22.25 m
Maximum lift radius : 20 m

Wireline Recorder

Manufacturer - Reliable Scale Corporation; Data recorded – weight, line speed, depth, time & date

BOP and Stuffing Box Control Panel

Max. W.P. – 210 bars / 3000 PSI; Placed in operator's cab for easy access

Safety devices

Air inlet shut off, spark arrestor, anti – static fan belts fitted

Dimensions

11.1 m (L) x 2.5 m (W) x 4.1 m (H); Weight = 22.5 t